

1/2" Hammer Drill / Driver DHP484 1/2" Drill / Driver DDF484









High speed **2,000** rpm

Predecessor model: 1,550 rpm

Compact overall length
7-1/8" (DHP484)

Predecessor model: 199 mm

## Aluminum gear housing and all metal gear construction

for extra-high transmission durability







| /2" Hammer Drill / Driver<br>/2" Drill / Driver |                     | DHP484 13 mm(1/2") DDF484 13 mm(1/2") |                      |
|---|---------------------|---------------------------------------|----------------------|
|   |                     |                                       |                      |
| E)  | Battery Capacities  | 18V Li-lon                            | 18V Li-lon           |
| Brake   | Capacities          | Concrete: 1/2" (13 mm)                | -                    |
|   |                     | Steel: 1/2" (13 mm)                   | Steel: 1/2" (13 mm)  |
| Reversing                                       |                     | Wood: 1-1/2" (38 mm)                  | Wood: 1-1/2" (38 mm) |
|   | No Load Speed       | Low: 0 - 500 RPM                      | Low: 0 - 500 RPM     |
| Mechanical 2-Speed                              |                     | High: 0 - 2,000 RPM                   | High: 0 - 2,000 RPM  |
|   | Blows Per Minute    | Low: 0 - 7,500 BPM                    | -                    |
| Keyless Chuck                                   |                     | High: 0 - 30,000 BPM                  | -                    |
|   | Maximum Lock Torque | 530 in. lbs. (60Nm)                   | 530 in. lbs. (60Nm)  |
| Torque Setting 21                               | Overall Length      | 7-1/8" (182 mm)                       | 6-3/4" (172 mm)      |
| Built-in Job Light                              |                     |                                       |                      |
| Carrying Case                                   |                     |                                       |                      |

## When QUALITY & SERVICE COUNTS – Choose Makita makita.ca