

SPERIAN PURE FIT™ GENERAL PURPOSE GLOVES

PRODUCT INFORMATION

Sizes Available	Part #	Overedge Colors	UPC
Small	372-S	Red	801462004052
Medium	372-M	Blue	801462004069
Large	372-L	Yellow	801462004076
XLarge	372-XL	White	801462004083



Shell Material:	Nylon	Material Color:	Black
Shell Weight:	13-cut, lightweight	Coating Color:	Black
Coating Material:	Nitrile; fully dipped hand	Case Qty:	144 pair
Coating Pattern:	Smooth finish	Country of Origin:	China

PRODUCT FEATURES

- Lightweight nylon provides excellent abrasion resistance
- Nitrile coating resists nicks, cuts, and abrasions
- Hand is fully coated for added resistance to liquid penetration
- Excellent tactile sensitivity

TESTING INFORMATION

	Test Method		Level	Test Result
Abrasion Resistance:	ASTM 3389-05		Level 4	≥ 3,000 cycles
	EN388		Level 4	≥ 8,000 cycles
Cut Resistance:	ASTM F1790-97		Level 2	≥ 500 grams
	EN388		Level 1	≥ 1,2 grams
Tear Resistance:	EN388		Level 2	≥ 25 newtons
Puncture Resistance:	EN388		Level 1	≥ 20 newtons

LAUNDERING INSTRUCTIONS

Product withstands commercial laundry-room detergents (up to pH 15) and warm water temperatures up to 120° F (49° C). Lower heat settings (up to 180° F) are suggested for drying as extreme heat may cause shrinking and degradation of fiber.



WARNINGS

- * Gloves are cut-resistant, not cut proof. Extreme caution should be used around moving machinery.
- ** Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness or death.

This information is provided as a guideline for product use. The end user is solely responsible for determining the suitability of a particular glove for a specific application and the length of time in which such glove may be safely used.

Hand protection with a Perfect Fit

Sperian Protection Americas, Inc. | 900 Douglas Pike, Smithfield, RI 02917-1874 | tel: 1.800.430.5490 | fax: 1.800.322.1330