

Product Family Uvex XV100 Series

Super-economy based eye protection.

Product Numbers & Ordering Information

	Product Numbers	Details
	XV100	Clear Frosted Frame Clear Lens, Anti-scratch Coating
	XV101	Gray Frosted Frame Gray Lens, Anti-scratch Coating
00	XV102	Clear Frosted Frame I/O Silver Mirror Lens, Anti-scratch Coating
	XV103	Clear Frosted Frame Clear Lens, Uvextra Anti-fog Coating
0	XV107	Clear Frosted Frame Clear Lens, Uncoated
	XV108	Gray Frosted Frame Gray Lens, Uncoated

Additional Information

800-430-5490 (US), 888-212-7233 (Canada)

Overview

Key Features

- 10-base, wrap-around uni-lens for great peripheral vision and protection
- Molded, universal nosepiece for easy fit
- · Lightweight design and thin, shaped temples for all-day comfort
- · Available in clear, gray, and indoor-outdoor silver mirror lens tints for a variety of applications
- Anti-scratch Hardcoat lenses for maximum durability
- Optional Uvextra® anti-fog coating available (Clear lens)

Hazards

Impact

Regulations

• ANSI - Meets ANSI Z87.1-2010 standard

Warranty Information

LIMITED WARRANTY Uvex Eye and Face Protection, Inc. warrants that its products are free from defects in material and workmanship. A product that is the subject of a warranty claim must first be made available to an authorized distributor or to the seller from whom the product was purchased. All warranty returns must be shipped pre-paid. Uvex will then determine whether repair or replacement of the product is the appropriate remedy. This will be done at no charge to the end user. This limited warranty does not cover any Uvex Eye and Face product or component found to have been altered, misused, abused tampered with or improperly maintained or to have deteriorated due to aging of any components made of rubber or any other elastomer. This limited warranty does not cover any damage, loss or expense due to damage caused by accident, abuse, improper maintenance, use or misuse of the product. Uvex Eye and Face products should only be used in strict accordance with and adherence to the detailed instructions and warnings provided with the product.

Specifications

Lens overall width

• 5.57" (139 mm) nominal

Lens material

Polycarbonate

Lens coating

• Uvextra Anti-fog. Anti-Scratch Coating

Lens thickness

• 0.098" (2.5mm) Minimum

Lens tints

• Clear, Standard Gray, I/O Silver

Replacement lenses available

No

Rx capable

No

Temple material

Polycarbonate

Temple length

• 4.7" (118.8mm)

Temple set-back

• 3" (75 mm)

Temple style

Skull wrap

Frame material

Polycarbonate

Frame colors

Uvex XV100 Series

• Clear, Standard Gray

Side shield material

• n/a

Dielectric frame

No

Packaging (spectacle)

• Ind. box, 10/stocker, 200/case

Country of origin

Taiwan

MSDS requirements

None

WHMIS requirements

None

Harmonization code

• 9004.90.0000

Literature & Documents

Uvex XV100 Series Brochure - English http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Eye_and_Face_Protection/Eyewear/4294990294/1033.aspx

Training & Proper Use

All products come packaged with instructions and warnings for proper use.

© Honeywell International Inc.